

5551 Corporate Boulevard, Suite 200
Baton Rouge, Louisiana 70808
Telephone: (225) 292-9007 Fax: (225) 952-2978

www.CRAworld.com

June 6, 2013

Reference No. 027545-00

Mr. Gary G. Miller Remedial Project Manager United States Environmental Protection Agency 6SF-RA 1445 Ross Avenue, Suite 1200 Dallas, Texas 75202

Dear Mr. Miller:

Re:

Final Feasibility Study Report Revised Pages

Star Lake Canal Superfund Site

Jefferson County, Texas

CERCLA Docket No. 06-02-06

Conestoga-Rovers & Associates (CRA) and Cardno ENTRIX, on behalf of Chevron Environmental Management Company (CEMC) and Huntsman Petrochemical LLC (Huntsman), submit herein to the U.S. Environmental Protection Agency (EPA) the revised pages for the Final Feasibility Study (FS) Report for the Star Lake Canal Superfund Site located in Jefferson County, Texas (Site). This correspondence includes only the revised report text page and tables. The attached revised pages should replace existing pages in the Final FS Report dated June 4, 2012. The Final FS Report includes the following revisions:

### REPORT TEXT

Revised report text includes page 199.

#### **TABLES**

Tables 6-7 and 7-7 were revised and are attached.

A complete electronic copy of the Final FS Report with the incorporated revisions will be submitted via email.

Should you have any questions regarding this submittal, please contact CRA or Mr. Gary Jacobson of CEMC at (713) 432-2636.

Yours truly,

**CONESTOGA-ROVERS & ASSOCIATES** 

Campbell

Pressley L. Campbell, PhD

**Texas PE 76931** 

PLC/kmc/1 Encl.



685626

Equal Employment Opportunity Employer

byrnent Opportunity
byer

ISO 9001

ENGINEERING DESIGN



June 6, 2013

cc:

Kenneth Shewmake, USEPA
Carlos Sanchez, USEPA
Barry Forsythe, USFWS
Jessica White, NOAA
Craig Giggleman, USFWS
Clare Lee, USFWS (electronic)
Jessica Mauricio, TCEQ (electronic)
Phillip Winsor, TCEQ
Richard Seiler, TCEQ
Larry Champagne, TCEQ
Tommy Mobley, TGLO
Mike Miller, Huntsman

-2-

Reference No. 027545-00

Don Pitts, TPWD
Andy Tirpak, TPWD
Gary Jacobson, CEMC
Jerry Hall, Chevron
Eve Barron, Chevron (electronic)
Marty Briggs, Huntsman (electronic)
Bret Duplant, Huntsman (electronic)
Bill Dugan, Huntsman (electronic)
Lon Tullos, Huntsman (electronic)
Barry Gillespie, Cardno ENTRIX
Karen Favret, Cardno ENTRIX (electronic)

of a 6-inch layer of clay, to inhibit infiltration, overlaid with a 6-inch layer of top soil to allow for vegetative stabilization. The MNR alternative lowers the risk of interaction between benthic invertebrates and the sediment very gradually. Overall protection of the environment depends upon the rate of naturally driven degradation and dispersion processes. Natural processes will be monitored by scheduled sampling events over the 10 year time period. Table 6-7 displays the cost summary to implement this alternative. The costs are separated into three categories: Base Implementation, Remediation and Disposal, and Present-Worth O&M Costs. Base Implementation Costs are defined as, but not limited to, equipment and personnel mobilization to and from the Site, pre-remediation Site work, facilities, and Site characterization sampling and analysis. Remediation and Disposal Costs are defined as, but not limited to, equipment (excavator, loader, trucks, etc.), operators (includes lodging, transportation, per diem and wages), materials (cap, backfill, pipe, etc.), and disposal costs of the off-Site disposal facility. All material, equipment, and disposal price calculations were based from verbal or written quotes obtained from licensed, regional vendors approved by the EPA and PRPs. Present Worth O&M Costs are defined as, but are not limited to, engineered monitoring equipment (including installation), annual maintenance, and monitoring. Maintenance and monitoring events are scheduled monthly for the first two years, quarterly for years three through five, and semiannually for the remainder of the 10-year time frame. Semiannual site inspections will be conducted every year in addition to the scheduled sampling events. Scheduled sampling events (years one, two, four, eight, and ten) will include extensive sediment and soil sample collection. Samples will be collected from the same vicinity to verify and validate a true representation of remedial progress over time. Monitoring events include sample collection and analysis to determine status and progress of remedial action implementation and a thorough AOI site inspection. All sample analysis costs were calculated from quotes obtained from a qualified laboratory.

## 6.8.4 ALTERNATIVE 2C - MONITORED NATURAL RECOVERY AND 12-INCH REMOVAL AND DISPOSAL AND CONTAINMENT: 12-INCH ARMORED CAP

This alternative utilizes MNR for the Molasses Bayou Waterway polygons that correspond to sample numbers MB-51, MB-56, MB-58, and MB-59; and 12-inch removal/disposal and containment with a 12-inch armored cap for the polygons that correspond to sample numbers MB-26 MB-62, and MB-63. Material will be excavated with hydraulic dredge equipment, staged in an area to be de-watered (by filter press or Geo-Tubes) and transported to a licensed off-Site disposal facility. A 12-inch armored backfill (layer of cobbles, pebbles or other large material and prohibits disturbance by its

#### TABLE 6-7

### ALTERNATIVE COST ESTIMATE FOR MOLASSES BAYOU WETLAND AOI STAR LAKE CANAL SUPERFUND SITE JEFFERSON COUNTY, TEXAS

Item	Alternative Description	Base Implementation Cost <sup>1</sup>	Remediation and Disposal Cost <sup>2</sup>	Present Worth Operation & Maintenance Cost <sup>3</sup>	Estimated Total Cost					
Alternat	Alternative 1- Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, MB-59, MB-62, and MB-63									
1	No action	\$0	\$0	\$0	\$0					
Alternat	Alternative 2 - Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, MB-59, MB-62, and MB-63									
2a	Monitored Natural Recovery	\$360,000	\$954,000	\$853,000	\$2,167,000					
2b	Monitored Natural Recovery and Containment: 12-inch Composite Cap	\$540,000	\$3,213,000	\$1,127,000	\$4,880,000					
<b>2</b> c	Monitored Natural Recovery and 12-inch Removal/Disposal and Containment: 12-inch Armored Cap	\$2,040,000	\$12,764,000	\$1,127,000	\$15,931,000					
2d	Monitored Natural Recovery and 12-inch Removal/Disposal	\$2,040,000	\$10,917,000	\$1,127,000	\$14,084,000					
Alternat	Alternative 3 - Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, MB-59, MB-62, and MB-63									
3	Containment without excavation: 12-inch Composite Cap	\$540,000	\$2,839,000	\$274,000	\$3,653,000					
Alternat	Alternative 4 - Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, MB-59, MB-62, and MB-63									
4	Partial 12-inch Removal/Disposal and Partial Containment: 12-inch Armored Cap	\$2,040,000	\$29,680,000	\$274,000	\$31,994,000					
Alternat	ive 5 - Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, N	IB-59, MB-62, and MB	-63							
5	Partial 12-inch Removal/Disposal	\$2,040,000	\$24,893,000	\$24,893,000 \$274,000						

Notes: 1. Base Implementation Cost includes mobilization/demobilization costs, site preparations and site characterization analyses costs

<sup>2.</sup> Treatment and Disposal Costs include: excavation, dredging, capping, backfill, other materials, and disposal costs at an offsite disposal facility

<sup>3.</sup> Present Worth O&M Cost includes: engineered monitoring equipment including installation, annual maintenance and monitoring. All costs are accrued for a 10-year term

#### TABLE 7-7

# COMPARATIVE ANALYSIS OF REMEDIAL ALTERNATIVES FOR MOLASSES BAYOU WETLAND AOI STAR LAKE CANAL SUPERFUND SITE JEFFERSON COUNTY, TEXAS

	Alternative Description	Threshold Criteria		Balancing Criteria					
Item		Overall Protection of the Environment	Compliance with ARARs	Long-Term Effectiveness	Reduction of Toxicity, Mobility, and Volume	Short-Term Effectiveness	Implementability	Cost	
Alternative 1- Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, MB-59, MB-62, and MB-63									
1	No Action	N	N	1	1	1	5	\$0	
Alternat	ive 2 - Polygons that correspond to sample numbers: MB-26, MB-5.	I, MB-56, MB-58, MB	-59, MB-62, and MB	-63					
2a	Monitored Natural Recovery	N	s	3	3	3	5	\$2,165,340	
2b	Monitored Natural Recovery and Containment: 12-inch Composite Cap	S	S	4	4	3	4	\$4,880,000	
2c	Monitored Natural Recovery and 12-inch Removal/Disposal and Containment: 12-inch Armored Cap	S	S	4	4	3	3	\$15,930,240	
2d	Monitored Natural Recovery and 12-inch Removal/Disposal	S	S	4	4	3	4	\$14,083,240	
Alternat	ive 3 - Polygons that correspond to sample numbers: MB-26, MB-5	1, MB-56, MB-58, MB	1-59, MB-62, and MB	-63					
3	Containment - without excavation: 12-inch composite cap	S	S	4	3	4	2	\$3,653,000	
Alternat	ive 4 - Polygons that correspond to sample numbers: MB-26, MB-5	1, MB-56, MB-58, MB	1-59, MB-62, and MB	-63					
4	Partial 12-inch Removal/Disposal and Partial Containment: 12-inch Armored Cap	N	S	5	5	4	1	\$31,994,000	
Alternat	Alternative 4 - Polygons that correspond to sample numbers: MB-26, MB-51, MB-56, MB-58, MB-59, MB-62, and MB-63								
5	Partial 12-inch Removal/Disposal	N	S	5	5	4	2	\$27,207,000	

Criteria and Numerical Scoring for Evaluation of Remedial Alternatives
Threshold Criteria: Minimum Requirements
N-Does not satisfy criterion
S-Satisfies criterion
Balancing Criteria: Multiple Criteria Simultaneously Considered
1 -Low
2-Low to Moderate
3-Moderate
4-Moderate to High
5-High